

2K SERIES: 2K2

Dimensions & Performance Characteristics

2K2 Series Mounts = 1.6 lbs.

Top View Dimensions:

- Overall width: $4.062 \pm .031$ [103.2] SQ
- Mounting hole diameter: $\varnothing 1.625$ * [Ø 41.3]
- Core diameter: $\varnothing 1.125$ * [Ø 28.6]
- Core length: $.625 \pm .016$ [15.9]
- Thread: $.375-16 \text{ UNC-2B}$
- Thread depth: $.562 \pm .016$ DEEP [14.3]

Side View Dimensions:

- Approx. free height for AA type: 3.156 [80.2]
- Approx. free height for BA type: 3.406 [86.5]
- Core length: $2.750 \pm .016$ [69.8] SQ
- Core diameter: $\varnothing .266 \pm .010$ [Ø 6.8]
- Core length tolerance: $.250 \pm .016$ * [6.4]
- Core diameter tolerance: $.062 \pm .016$ [1.6]
- Max. core length: $.5 \text{ MAX}$

Bottom View Dimensions:

- Overall width: $4.000 \pm .031$ [101.6] SQ
- Mounting hole diameter: $\varnothing .266 \pm .010$ [Ø 6.8]
- Feature: THRU METAL INSERT 4 HOLES

*** PLEASE NOTE: On 2K1 and 2K2 Isolators, -AA part number indicates a short core for use with dimpled mounting trays. -BA part number indicates a long core for attachment directly to equipment.**

2K2 LOAD RATINGS	
PART #	STATIC LOAD RANGE /ISOLATOR (LBS.)
2K2-AA-6 & BA-6	4-6
2K2-AA-10 & BA-10	6-10
2K2-AA-16 & BA-16	10-16
2K2-AA-25 & BA-25	16-25
2K2-AA-40 & BA-40	25-40
2K2-AA-60 & BA-60	40-60
2K2-AA-75 & BA-75	60-75
2K2-AA-90 & BA-90	75-90

