

# NAVY MOUNT SERIES: UBST & EES BACK-TO BACK MOUNTS

## Dimensions & Performance Characteristics

### UBST Un-bonded Spool Mount Series

BARRY PART NO.	Ø B	C	D	Ø E	Ø F	*A* THREAD SIZE
21482-1	1.250 [31.8]	3.000 [76.2]	.250 [6.4]	.875 [22.2]	1.000 [25.4]	.312-18 UNC-2A
21482-2	1.750 [44.4]	4.250 [108]	.375 [9.5]	1.250 [31.8]	1.438 [36.5]	.375-16 UNC-2A
21482-3	2.000 [50.8]	5.000 [127]	.500 [12.7]	1.438 [36.5]	1.688 [42.9]	.500-13 UNC-2A
21482-4	2.250 [57.2]	5.250 [133.4]	.625 [15.9]	1.625 [41.3]	2.000 [50.8]	.625-11 UNC-2A

Part #	Navy Type #	Capacity (lbs)
21482-1	UBST-15	15
21482-2	UBST-50	50
21482-3	UBST-100	100
21482-4	UBST-200	200
22416-1	6E100BB	100
22417-1	6E150BB	150
31114-5	6E900BB	900
31115-2	7E450BB	450

### EES Back-to-Back Series

BARRY PART NO.	A	B	Ø C	D	E	Ø F	Ø G	H
22416-1	5.875 [149.2]	4.750 [120.6]	3.000 [76.2]	4.312 [109.5]	.875 [22.2]	.640 [16.3]	.531 [13.5]	3.375 [85.7]
22417-1	6.625 [168.3]	5.375 [136.5]	3.250 [82.6]	4.562 [115.9]	1.000 [25.4]	.640 [16.3]	.656 [16.7]	3.500 [88.9]
31114-5	9.750 [247.6]	8.250 [209.6]	5.500 [139.7]	6.125 [155.6]	.990 [25.2]	1.062 [27]	.781 [19.8]	7.500 [190.5]
31115-2	6.500 [165.1]	5.375 [136.5]	3.500 [88.9]	4.625 [114.5]	.875 [22.2]	.812 [20.6]	.656 [16.7]	4.000 [101.6]